

# Sentry Cleaner & Safety Treatment

## Distributor

Slip and Fall Solutions, Inc.  
P.O. Box 4848  
Winter Park, FL  
32793  
Phone: (416) 256 4335  
E-mail: info@slipandfallsolutions.com

## Product Description

Sentry Cleaner & Safety Treatment is a one step process to clean floors and increase coefficient of friction (dry surfaces) and slip resistance (wet surfaces). Sentry is used on vinyl, linoleum, wood, and other resilient floor materials. Sentry may also be used on acrylic sealers, waxes, waxed and polished finishes or synthetic or carnauba waxes. It is also effective in damp mopping, spray buffing and machine scrubbing operations.

Sentry is supplied as a concentrate and, as a one step process, is more practical and economical (labor and product cost) to use than multiple floor products. Sentry will leave a shiny surface and can also be buffed to a high shine finish.

## Suggested surfaces

- 1) Wax – wood, vinyl, linoleum, marble, stone
- 2) 'Wet look' high gloss – vinyl, linoleum
- 3) Terrazzo
- 3) Urethane – wood – low or high gloss finish
- 4) Epoxy - test for suitability before general use

## Composition and Materials

Sentry is a concentrated film forming surface cleaner, maintainer, restorer and safety treatment in a single use product that combines cleaning agents, polymeric compounds, defoamers and neutralizing agents. Designed for commercial and industrial use it is water based, non-toxic, and nonflammable. Sentry does not fall into a specific generic classification and is a proprietary product manufactured under a closely held process.

## Limitations

Sentry is not intended for exterior use or use on glazed or unglazed ceramic tile, quarry tile, cement, pool decks or porcelain and ceramic bathtubs. Use *NO-Slip Treatment* for these surfaces. Solid surface and seamless epoxy floors should be tested for suitability before general use.

Do not mix Sentry with any other chemicals. Use cold water to dilute in accordance with application instructions.

## Technical Data

Diluents: Water	Cleanup: Water
Toxicity: None	Fumes: None
Flammability: None	
Freeze Harm: None	
Freeze Temperature: 32 degrees F	

## Application Directions

**Preparatory work:** Thorough dust mopping or sweeping to remove loose debris prior to application.

**Daily Cleaning/Safety Treatment:** Mix 2 oz. of Sentry per gallon of cold water and apply with a mop. Rinsing is not required, but if selected, adjust concentration to 4 oz. per gallon.

**Heavily Soiled Floors/Safety Treatment:** Mix 4 oz. Sentry per gallon of cold water. Scrubbing recommended. If necessary mop twice with Sentry mixture.

**Initial High Gloss Restoration/Safety Treatment:** Mix 8 oz. of Sentry per gallon of cold water. On a clean floor mop an even, wet coat of the mixture and let dry. Buff the entire area.

**Waxed Surfaces/Safety Treatment:** See 'Daily Cleaning' or 'Initial High Gloss Restoration'. Buff the entire area if high shine desired

**Spray Buffing/Safety Treatment:** Mix 1 part Sentry to 10 parts cold water and apply with a

trigger sprayer. Use high speed or standard speed equipment.

## Automatic Scrubbers

Use red or white scrub pads

**Initial Cleaning/Slip Treatment:** mix 8 oz. Sentry per gallon of cold water.

**Daily Cleaning:** mix 2 oz. Sentry per gallon of cold water.

**Heavily Soiled Floor:** mix 4 oz. Sentry per gallon of cold water.

## Clean up

Clean application tools, machinery and spills with clean water.

## For Optimum Results

- DO NOT mix with other chemicals
- Water rinse is not required
- Use cold water to extend longevity of finish
- Use Sentry as a daily cleaning/safety program

**NOTE:** Sentry's surface film will be removed by normal cleaning. In order to maintain the benefits of the product Sentry should be included in normal and scheduled floor maintenance procedures.

The use of Sentry Floor Safety Treatment is not intended to replace normal care and caution on dry or wet surfaces.

## WARRANTY

Slip and Fall Solutions, Inc. and Omni Advanced Concepts Inc. (herein known as Sentry Cleaner & Safety Treatment or Sentry) warrant that its products are free from manufacturing defects.

This warranty shall be valid only in those instances where Sentry Floor Safety Treatment has been correctly applied to a properly prepared surface and following the application procedures approved by Sentry.

Failure to remove all contaminants prior to or after treatment, including but not limited to grease, oils, or other contaminants shall void

this warranty. Use of sealants, waxes, grease, oils, or other coatings on the surface after the Sentry Cleaner & Safety Treatment shall void this warranty.

Sentry shall replace or refund the cost of any Sentry Cleaner & Safety Treatment product proven to be defective, such action being the exclusive remedy under this warranty. This Warranty takes precedence over any and all other warranties, expressed or implied, including the warranty of merchantability and fitness of purpose. Customer acknowledges that no other representations have been made to him or relied upon by him with respect to the quality and function of the Sentry Cleaner & Safety Treatment.

Sentry claims only that its products will clean and increase the slip resistance and are designed to reduce the risk of slip and fall accidents on wet surfaces to which the Sentry Floor Safety Treatment has been applied in accordance to application procedures approved by Sentry. Sentry, its distributors, dealers, agents, and representatives do not warrant or guarantee to the customer or any other party against the occurrence of slip and fall accidents, personal injury or property damage of any nature. Accidents or falls may occur on treated surfaces notwithstanding treatment with Sentry Cleaner & Safety Treatment and the customer agrees to indemnify and hold Sentry, its distributors, dealers, agents and representatives free and harmless from any incidental, consequential, sequential or sub sequential damages, claims, demands or causes of action arising in connection with or brought by anyone allegedly slipping, falling, tripping or stumbling on the treated area(s). No modification, addendum or additions to this warranty may be made.